

# SpeedStar®

## Category 5e Patch Cords

Suttle Category 5e rated patch cords provide performance that exceeds EIA/TIA-568-B.2 specifications for Category 5e channel, basic link, and component performance.



Product is available in a variety of colors for easy identification.

The easily depressed latch mechanism makes it a snap to insert and unplug

Molded boot provides bend radius protection

### Category 5e Patch Cord Specifications

<b>Conductors:</b>	24 AWG 7/32 stranded copper
<b>Insulation:</b>	Flame retardant polyethylene
<b>Jacket:</b>	PVC
<b>Wiring:</b>	Compatible with T568A and T568B.
<b>Contacts:</b>	Phosphor bronze with 100 micro-inch nickel with minimum 50 microinch gold plating
<b>Plastic Plug:</b>	High impact, UL 94V-0 rated thermoplastic.
<b>Insulation Resistance:</b>	500 megaohms minimum
<b>Contact Resistance:</b>	20 milliohms maximum
<b>Current Rating:</b>	1.5 amps at 68 Deg F per IEC Publication 512-3, test 5b
<b>Dielectric Withstand:</b>	1000 VAC RMS @ 60 Hz minimum
<b>Current Rating:</b>	1.5 amps at 68 Deg F per IEC Publication 512-3, test 5b Complies with TIA/EIA Category 5e Specifications

### Ordering Info

Part Number	Description	Color	Pkg. Qty.
2-7403-xx	3-ft Cat 5e Patch Cord	(53) Red, (56) Yellow, (62) Blue	1
2-7407-xx	7-ft. Cat 5e Patch Cord	(53) Red, (56) Yellow, (62) Blue	1
2-7410-xx	10-ft Cat 5e Patch Cord	(53) Red, (56) Yellow, (62) Blue	1
2-7415-xx	15-ft Cat 5e Patch Cord	(53) Red, (56) Yellow, (62) Blue	1

Additional sizes and colors may be available by request

CONTACT US  
223 Main St. South • Hector, MN 55342  
Ph: 320-848-6711 or 800-852-8662  
[www.suttleonline.com](http://www.suttleonline.com)

03-5ePC  
© 2003 Suttle, a subsidiary of Communications Systems, Inc.  
SpeedStar, Suttle, and the Suttle Logo are registered trademarks of Suttle, a subsidiary of Communications Systems, Inc.

# SUTTLE