

Suttle Fiber Bulkhead Interconnect Adapters

Product Description

Suttle bulkhead interconnect adapters are constructed with phosphorus bronze or zirconia sleeves, providing proper ferrule alignment for both singlemode and multimode applications. Ideal for use with Suttle AFP and ATC fiber panels. Packaging includes dust caps, press fit bushing, and a nut and lock washer to facilitate panel mounting

Features

- ◆ ST, FC, SC, and Hybrid SC to ST
- ◆ Zirconia or Phosphor Bronze sleeve
- ◆ Multimode or Singlemode fiber type
- ◆ Meets IEC, FOTP, and EIA/TIA performance standards
- ◆ For use with AFP and ATC fiber panels

Specifications

- ◆ Insertion Loss: 0.1 dB avg.
- ◆ Operational Temperature -40° C to +80° C

Part Numbers

FC

- ◆ AFCB-03-N Bright nickel plating, phosphor bronze sleeve, SM or MM
- ◆ AFCB-03-N-C Bright nickel plating, zirconia sleeve, SM only
- ◆ AFCB-03-D Bright nickel plating, phosphor bronze sleeve, SM or MM
- ◆ AFCB-03-D-C Bright nickel plating, zirconia sleeve, SM only

ST

- ◆ ASTA-03-B Black nickel plating, phosphor bronze sleeve, SM or MM
- ◆ ASTA-03-N Bright nickel plating, phosphor bronze sleeve, SM or MM
- ◆ ASTB-03-N Bright nickel plating, zirconia sleeve, SM only

SC

- ◆ ASCAS-03-62 SC simplex, phosphor bronze sleeve, SM or MM
- ◆ ASCBS-03-62 SC simplex, zirconia sleeve, SM only
- ◆ ASCAD-03-62 SC duplex, phosphor bronze sleeve, SM or MM
- ◆ ASCBD-03-62 SC duplex, zirconia sleeve, SM only
- ◆ ASCAPC-03-N SC simplex, APC zirconia, SM only

Hybrid SC to ST

- ◆ ASCSTAD-03-62 Blue, phosphor bronze sleeve, SM only
- ◆ ASCTAD-03-62 Beige, phosphor bronze sleeve, MM only



AFCB-03-N



AFCB-03-D-C



ASTA-03-B

ASTA-03-N

ASTB-03-N



ASCAS-03-62



ASCTAD-03-62